


AGRIMAX TERIS

	520/85 R 42
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	BIÇERDÖVER / PAMUK TOPLAMA MAKINESİ
VERSION	STANDARD
TIRE TYPE	TL
	168 D



UNDEFINED US STANDARD

USA CODE	94044634	RC (IN)	230.4
SW (IN)	20.3	RIM REC	DW 16 L
OD (IN)	76.8	RIM ALT	W15L; DW15L; DD16L; W16L; DD18L; DW18L; W18L
SLR (IN)	35.0	ECE	E4-106R-001829

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35	41	46	55
40	4080	4820	5560	6170	6920	7540	8770	10010	11240	12350	-
30	4290	5060	5840	6480	7260	7910	9200	10500	11810	12960	-
25	4460	5280	6100	6770	7580	8260	9610	10960	12310	13520	-
20	4700	5540	6390	7100	7960	8660	10090	11510	12930	14200	-
15	4840	5710	6590	7320	8200	8940	10390	11860	13330	14640	-
5	6120	7230	8330	9260	10370	11300	13150	15000	16850	18520	-
5 CYC*	-	-	-	-	-	-	-	-	-	-	20990

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.