

FLOTATION 648

TIRE SIZE	700/40 - 22.5
UM	IS STANDARD
CONSTRUCTION	⊠ BIAS
MACHINERY	ENFARDADEIRA DE FENO / CEIFEIRA / ESPALHADOR / CEIFEIRA / IMPLEMENTOS AGRÍCOLAS
VERSÃO	STANDARD
TIRE TYPE	TL
LI/SS DRIVE WHEEL	148 A8/144 B
LI/SS FREE ROLLING	160 A8/ 157 B



DIMENSÕES IS STANDARD

SW (MM)	700	RIM REC	AG 24.00
OD (MM)	1170	ECE	E11-106R-004554
SLR (MM)	510	PR	12
RC (MM)	3537		

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	1.50	1.60	1.70
10 FR	5850	6085	6300
20 FR	5265	5475	5670
30 FR	4680	4865	5040
40 FR	4180	4345	4500
50 FR	3760	3910	4125
10 DW	4100	4255	4410
20 DW	3690	3830	3970
30 DW	3280	3405	3530
40 DW	2930	3040	3150
50 DW	2635	2735	2800

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.