

# FLOTATION 648

<b>TIRE SIZE</b>	<b>700/40 - 22.5</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	⊠ BIAS
<b>MACHINERY</b>	HEUPRESSE / ERNTEMASCHINE / STREUMASCHINE / ERNTEMASCHINE / LANDWIRTSCHAFTLICHE GERÄTE
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	148 A8/144 B
<b>LI/SS FREE ROLLING</b>	160 A8/ 157 B



## ABMESSUNGEN US STANDARD

<b>USA-CODE</b>	94006472	<b>RC (IN)</b>	139.3
<b>SW (IN)</b>	27.6	<b>RIM REC</b>	AG 24.00
<b>OD (IN)</b>	46.1	<b>ECE</b>	E11-106R-004554
<b>SLR (IN)</b>	20.1	<b>PR</b>	12

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	22	23	25
<b>5 FR</b>	12900	13410	13890
<b>10 FR</b>	11610	12070	12500
<b>20 FR</b>	10320	10720	11110
<b>25 FR</b>	9210	9580	9920
<b>30 FR</b>	8290	8620	9090
<b>5 DW</b>	9040	9380	9720
<b>10 DW</b>	8130	8440	8750
<b>20 DW</b>	7230	7510	7780
<b>25 DW</b>	6460	6700	6940
<b>30 DW</b>	5810	6030	6170

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.