


# AIROMAX AM 27

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | <b>445/80 R 25</b>   |
| <b>UM</b>           | US STANDARD  |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | GRUE AUTOMOTRICE   |
| <b>VERSION</b>      | STANDARD   |
| <b>TIRE TYPE</b>    | TL   |
| <b>LI/SS</b>        | 170 F  |



## DIMENSIONS US STANDARD

|                 |          |                |                 |
|-----------------|----------|----------------|-----------------|
| <b>CODE USA</b> | 94076291 | <b>RIM REC</b> | 14.00/1.5       |
| <b>OD (IN)</b>  | 53.1     | <b>RIM ALT</b> | 14.00/1.3       |
| <b>SLR (IN)</b> | 24.8     | <b>ECE</b>     | E11-54R-0022144 |
| <b>RC (IN)</b>  | 162.0    |                |                 |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 76    | 80    | 83    | 87    | 91    | 94    | 98    | 102   |
|-----------|-------|-------|-------|-------|-------|-------|-------|-------|
| 50        | 10500 | 11000 | 11400 | 11700 | 12000 | 12300 | 12800 | 13200 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.