

# AS 504

<b>TIRE SIZE</b>	<b>6.00 - 16</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	
<b>MACHINERY</b>	TELEHANDLER / FIELD TRAILER / IMPLEMENTS / TELEHANDLER
<b>VERSION</b>	HD
<b>TIRE TYPE</b>	TT
<b>LI/SS DRIVE WHEEL</b>	83 A8
<b>LI/SS FREE ROLLING</b>	95 A8



## DIMENSIONS IS STANDARD

<b>SW (MM)</b>	164	<b>RIM REC</b>	4.00 E
<b>OD (MM)</b>	735	<b>RIM ALT</b>	4.50 E; 4½ K
<b>SLR (MM)</b>	343	<b>ECE</b>	E11-106R-005194
<b>RC (MM)</b>	2190	<b>PR</b>	6

## LOAD CAPACITY (KG/TIRE)

<b>KM/H / BAR</b>	<b>2.80</b>
10 FR	965
25 FR	820
30 FR	775
40 FR	690
10 DW	680
25 DW	575
30 DW	545
40 DW	485

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.