

# EARTHMAX SR 55

<b>TIRE SIZE</b>	<b>18.00 R 25</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	БУЛЬДОЗЕР / ПОГРУЗОЧНО-ДОСТАВОЧНАЯ МАШИНА / ПОГРУЗЧИК
<b>VERSION</b>	CUT RESISTANT COMPOUND
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	206 A2



## РАЗМЕРЫ IS STANDARD

<b>OD (MM)</b>	1667	<b>TRA CODE</b>	L55
<b>SLR (MM)</b>	733	<b>STAR RATING</b>	★★★
<b>RC (MM)</b>	4852		
<b>RIM REC</b>	13.00/2.5		

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	5.50	5.75	6.00	6.25	6.50	6.75	7.00	7.25	7.50	7.75	8.00	8.25	8.50	8.75	9.00
10	11800	12150	12500	12850	13200	13600	14000	14500	15000	15000	15500	16000	16500	16500	17000

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.