

FLOTATION 648

TIRE SIZE	650/65 - 30.5
UM	US STANDARD
CONSTRUCTION	⊠ BIAS
MACHINERY	HEUPRESSE / ERNTEMASCHINE / STREUMASCHINE / ERNTEMASCHINE / LANDWIRTSCHAFTLICHE GERÄTE
VERSION	HD
TIRE TYPE	TL
LI/SS DRIVE WHEEL	169 A8/165 B
LI/SS FREE ROLLING	181 A8/178 B



ABMESSUNGEN US STANDARD

USA-CODE	94030279	RC (IN)	194.3
SW (IN)	26.4	RIM REC	AG 20.00
OD (IN)	65.4	ECE	E11-106R-004563
SLR (IN)	28.0	PR	18

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	33	35	36
5 FR	24240	24860	25460
10 FR	21810	22380	22920
20 FR	19400	19880	20370
25 FR	17320	17760	18190
30 FR	15590	15980	16530
5 DW	17050	17480	17900
10 DW	15340	15740	16110
20 DW	13650	13990	14320
25 DW	12180	12490	12790
30 DW	10970	11240	11350

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.