


AGRIMAXFACTOR

TIRE SIZE	620/70 R 38
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	ТРАКТОР-ТЯГАЧ
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	170 D ; 173 A8



РАЗМЕРЫ US STANDARD

USA CODE	94076444	RC (IN)	219.7
SW (IN)	24.6	RIM REC	DW 20 B
OD (IN)	72.2	RIM ALT	DW 18 L; W 18 L
SLR (IN)	33.2	ECE	E11-106R-0010338

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35	41	47
40	5590	6590	7590	8450	9460	10320	11320	12180	12300	13230
30	5870	6920	7980	8880	9930	10840	11890	12800	12920	13890
25	6130	7230	8320	9270	10360	11310	12400	13350	13480	14480
15	6440	7580	8740	9730	10880	11870	13030	14010	14150	15210
5 LT	7500	8840	10180	11330	12680	13830	15180	16320	16490	17720
5 HT	6440	7580	8740	9730	10880	11870	13030	14010	14150	15210

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.