

AGRIMAX RT 855

TIRE SIZE	480/80 R 46
UM	US STANDARD
MACHINERY	PULVÉRISATEUR / MACHINE À VENDANGER / TRACTEUR / MOISSONNEUSE / OUTILLAGE AGRICOLE
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	158 A8/B



DIMENSIONS US STANDARD

CODE USA	94021826	RC (IN)	231.1
SW (IN)	18.9	RIM REC	DW 16 A ; W 16 A ; DD 16
OD (IN)	76.2	RIM ALT	W 16 L ; DD 16 L ; DW 16 L
SLR (IN)	35.2	ECE	E4-106R-001731

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35
30	4410	5060	5810	6560	7310	8060	8720	9350
25	4410	5060	5810	6560	7310	8060	8720	9350
20	4720	5420	6230	7020	7830	8630	9340	10030
5 LT	5910	6790	7790	8800	9800	10800	11680	12550
5 HT	4720	5420	6230	7020	7830	8630	9340	10030

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.