


AW 711

TIRE SIZE	265/70 R 16.5
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	MAȘINĂ DE RECOLTARE / MAȘINI DE IMPLEMENTARE / MAȘINĂ DE RECOLTARE / MAȘINI DE IMPLEMENTARE
VERSION	STUBBLE RESISTANT
TIRE TYPE	TL
LI/SS	134 A8/B



DIMENSIUNI US STANDARD

USA CODE	94053292	RC (IN)	90.0
SW (IN)	10.4	RIM REC	8.25
OD (IN)	30.4	ECE	E11-106R-002978
SLR (IN)	13.5		

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	12	17	23	29	35	41	46	52	58
30	1500	1970	2390	2770	3190	3600	3880	4250	4670
25	1500	1970	2390	2770	3190	3600	3880	4250	4670
20	1680	2200	2680	3100	3560	4030	4350	4770	5240
15	1790	2350	2840	3280	3790	4290	4630	5070	5570
10	1900	2480	3010	3480	4010	4540	4910	5370	5900
5	2110	2760	3340	3870	4450	5050	5450	5960	6550

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.