


AW 711

TIRE SIZE	380/70 R 19.5
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	КОМБАЙН / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ / КОМБАЙН / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ
VERSION	STUBBLE RESISTANT
TIRE TYPE	TL
LI/SS	159 A8/B



РАЗМЕРЫ IS STANDARD

SW (MM)	389	RIM REC	11.75
OD (MM)	1019	RIM ALT	12.75
SLR (MM)	444	ECE	E11-106R-006808
RC (MM)	3038	SRI	475

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.8	1.2	1.6	2	2.4	2.8	3.2	3.6	4	5	5.5
50	1295	1665	2035	2345	2715	3085	3305	3655	4005	4115	4375
40	1295	1665	2035	2345	2715	3085	3305	3655	4005	4115	4375
30	1450	1865	2280	2625	3040	3455	3700	4095	4485	4610	4900
25	1540	1980	2425	2790	3235	3675	3935	4355	4770	4900	5210
20	1630	2100	2565	2955	3420	3890	4165	4610	5050	5185	5515
10	1810	2330	2850	3280	3800	4320	4625	5115	5605	5760	6125

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.