

# FLOTATION TR 675

|                           |  |
|---------------------------|--|
| <b>TIRE SIZE</b>          | <b>550/60 - 22.5</b>                       |
| <b>UM</b>                 | US STANDARD                                |
| <b>CONSTRUCTION</b>       | ❖ BIAS                                     |
| <b>MACHINERY</b>          | IMPLEMENT MACHINERY / TRAILER / IMPLEMENTS |
| <b>VERSION</b>            | STANDARD                                   |
| <b>TIRE TYPE</b>          | TL   |
| <b>LI/SS DRIVE WHEEL</b>  | 154 A8/150 B                               |
| <b>LI/SS FREE ROLLING</b> | 167 A8/163 B                               |



## DIMENSIONS US STANDARD

|                 |          |                |                 |
|-----------------|----------|----------------|-----------------|
| <b>USA CODE</b> | 94019816 | <b>RC (IN)</b> | 143.3           |
| <b>SW (IN)</b>  | 21.7     | <b>RIM REC</b> | AG 16.00        |
| <b>OD (IN)</b>  | 49.6     | <b>ECE</b>     | E11-106R-004397 |
| <b>SLR (IN)</b> | 21.5     | <b>PR</b>      | 16              |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI    | 35    | 38    | 41    |
|--------------|-------|-------|-------|
| <b>5 FR</b>  | 15370 | 16110 | 16820 |
| <b>10 FR</b> | 13830 | 14490 | 15130 |
| <b>20 FR</b> | 12300 | 12890 | 13460 |
| <b>25 FR</b> | 10980 | 11510 | 12010 |
| <b>30 FR</b> | 9880  | 10360 | 10750 |
| <b>5 DW</b>  | 10570 | 11080 | 11570 |
| <b>10 DW</b> | 9510  | 9980  | 10420 |
| <b>20 DW</b> | 8450  | 8860  | 9260  |
| <b>25 DW</b> | 7550  | 7910  | 8270  |
| <b>30 DW</b> | 6800  | 7120  | 7390  |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.