

# AGRIMAX RT 855

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | <b>480/80 R 50</b>   |
| <b>UM</b>           | IS STANDARD  |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | PULVERIZADOR AGRÍCOLA /<br>VINDIMADORA / TRATOR / CEIFEIRA /<br>IMPLEMENTOS AGRÍCOLAS    |
| <b>VERSÃO</b>       | STEEL BELTED   |
| <b>TIRE TYPE</b>    | TL   |
| <b>LI/SS</b>        | 176 A8   |



## DIMENSÕES IS STANDARD

|                 |      |                |                 |
|-----------------|------|----------------|-----------------|
| <b>SW (MM)</b>  | 489  | <b>RIM REC</b> | DW 16 L         |
| <b>OD (MM)</b>  | 2036 | <b>RIM ALT</b> | DW 15 L; W 15 L |
| <b>SLR (MM)</b> | 945  | <b>ECE</b>     | E4-106R-001495  |
| <b>RC (MM)</b>  | 6183 | <b>SRI</b>     | 975             |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR   | 0.6  | 0.8  | 1.0  | 1.2  | 1.4  | 1.6  | 2.0  | 2.4  | 2.8  | 3.2  | 3.6  | 4.0  | 4.4  | 5.0  |
|--------------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|
| <b>50</b>    | 2060 | 2365 | 2715 | 3065 | 3415 | 3765 | 4070 | 4375 | 4760 | 5185 | 5470 | 5825 | 6320 | 7100 |
| <b>40</b>    | 2060 | 2365 | 2715 | 3065 | 3415 | 3765 | 4070 | 4375 | 4760 | 5185 | 5470 | 5825 | 6320 | 7100 |
| <b>30</b>    | 2205 | 2530 | 2905 | 3280 | 3655 | 4030 | 4360 | 4685 | 5095 | 5550 | 5855 | 6235 | 6765 | 7600 |
| <b>10 LT</b> | 2760 | 3170 | 3640 | 4110 | 4575 | 5045 | 5455 | 5865 | 6380 | 6950 | 7330 | 7805 | 8470 | 9515 |
| <b>10 HT</b> | 2205 | 2530 | 2905 | 3280 | 3655 | 4030 | 4360 | 4685 | 5095 | 5550 | 5855 | 6235 | 6765 | 7600 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.