

AS 504

TIRE SIZE	7.50 - 18
UM	US STANDARD
CONSTRUCTION	⊠ BIAS
MACHINERY	ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК / ПРИЦЕП ДЛЯ ПОЛЕВЫХ РАБОТ / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ / ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК
VERSION	STANDARD
TIRE TYPE	TT
LI/SS DRIVE WHEEL	101 A8
LI/SS FREE ROLLING	114 A8



РАЗМЕРЫ US STANDARD

USA CODE	94019366	RC (IN)	104.3
SW (IN)	8.2	RIM REC	5.50 F
OD (IN)	33.6	RIM ALT	4.50 E; 6.00 F; 5.00 F
SLR (IN)	16.0	ECE	E4-106R-002638

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	45
5 FR	3640
15 FR	3100
20 FR	2910
25 FR	2600
5 DW	2550
15 DW	2160
20 DW	2040
25 DW	1820

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.