


AGRIMAX RT 600

| | |
|---------------------|--|
| TIRE SIZE | 750/70 R 26 |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | ERNTEMASCHINE / STREUMASCHINE / TRACTOR / LANDWIRTSCHAFTLICHE GERÄTE |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 172 A8/B |



ABMESSUNGEN US STANDARD

| | | | |
|-----------------|----------|----------------|-----------------|
| USA-CODE | 94073146 | RC (IN) | 207.4 |
| SW (IN) | 30.7 | RIM REC | DW 25 B |
| OD (IN) | 68.9 | RIM ALT | DW 24 B |
| SLR (IN) | 30.9 | ECE | E11-106R-007934 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 9 | 12 | 15 | 17 | 20 | 23 | 29 | 35 | 41 | 46 | 52 |
|-----------|------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| 30 | 5970 | 6940 | 7930 | 8900 | 9780 | 10840 | 11950 | 12640 | 13890 | - | - |
| 25 | 5970 | 6940 | 7930 | 8900 | 9780 | 10840 | 11950 | 12640 | 13890 | - | - |
| 20 | 6400 | 7440 | 8490 | 9520 | 10570 | 11610 | 12800 | 13550 | 14880 | - | - |
| 5 LT | 8010 | 9310 | 10630 | 11930 | 13230 | 14540 | 16030 | 16950 | 18630 | - | - |
| 5 HT | 6400 | 7440 | 8490 | 9520 | 10570 | 11610 | 12800 | 13550 | 14880 | - | - |
| 5 CYC | - | 11170 | 12730 | 14290 | 15850 | 17420 | 19200 | 20310 | 22320 | 22670 | 23610 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.