


# AGRIMAX RT 600

IF 710/75 R 34

UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	BIÇERDÖVER / YAYICI / TRAKTÖR / UYGULAMALI MAKINE
VERSION	STEEL BELTED
TIRE TYPE	TL
	184 A8/B



## UNDEFINED US STANDARD

USA CODE	94512317	RC (IN)	227.2
SW (IN)	28.1	RIM REC	DW25 B
OD (IN)	75.6	RIM ALT	DW23 B
SLR (IN)	33.7	ECE	E11-106R-0010577

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35	41	46
30	7740	9130	10520	11710	13090	14290	15670	16860	18450	19840
25	7740	9130	10520	11710	13090	14290	15670	16860	18450	19840
10	8910	10500	12100	13470	15070	16430	18030	19400	21230	22820
5	9830	11600	13360	14870	16630	18140	19910	21430	23430	25200
UPTO 20 CYC	10060	11870	13680	15220	17030	18570	20380	21920	24000	25790
UPTO 10 CYC	12000	14150	16300	18150	20300	22140	24300	26150	28600	30750
UPTO 5 CYC	13160	15520	17880	19910	22270	24290	26650	28670	31370	33730

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.