



PRINTED ON  
23-04-2026

DATA SHEET

# XL GRIP IND3 (ECH)

|                     |                       |
|---------------------|-----------------------|
| <b>TIRE SIZE</b>    | <b>18.00 - 25</b>     |
| <b>UM</b>           | US STANDARD           |
| <b>CONSTRUCTION</b> | ⊠ BIAS                |
| <b>MACHINERY</b>    | TOMCONTAINERHANTERARE |
| <b>VERSION</b>      | PORT INDUSTRIAL       |
| <b>TIRE TYPE</b>    | TL                    |



## DIMENSIONER US STANDARD

|                 |          |                 |           |
|-----------------|----------|-----------------|-----------|
| <b>USA CODE</b> | 94049035 | <b>RIM REC</b>  | 13.00/2.5 |
| <b>OD (IN)</b>  | 63.6     | <b>RIM ALT</b>  | 15.00/2.5 |
| <b>SLR (IN)</b> | 29.1     | <b>PR</b>       | 32        |
| <b>RC (IN)</b>  | 188.2    | <b>TRA CODE</b> | IND3      |

## LOAD CAPACITY (LBS/TIRE)

| <b>MPH / PSI</b> | <b>131</b> |
|------------------|------------|
| 5                | 44600      |
| 15               | 41300      |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.