


AGRIMAX RT 600

TIRE SIZE	800/65 R 32
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	MAȘINĂ DE RECOLTARE / MAȘINĂ DE ÎMPRĂȘTIAT / TRACTOR / MAȘINI DE IMPLEMENTARE
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	181 A8 ; 178 B



DIMENSIUNI US STANDARD

USA CODE	94039302	RC (IN)	218.8
SW (IN)	30.5	RIM REC	DW 27 B
OD (IN)	71.7	RIM ALT	DH 27 B; DW 25 B
SLR (IN)	32.4	ECE	E4-106R-001429

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	12	15	17	23	29	35	41	46	52	58	64
30	7000	8070	9890	10800	11870	12930	14000	15210	16530	-	-
25	7610	8760	10750	11740	12900	14050	15210	16530	18190	-	-
20	8150	9380	11510	12570	13800	15050	16280	17690	19470	-	-
5 LT	10200	11750	14410	15740	17280	18840	20390	22160	24370	-	-
5 HT	8150	9380	11510	12570	13800	15050	16280	17690	19470	-	-
5 CYC	-	12470	15940	17550	20390	22350	24370	26510	27420	28660	30860

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.