

# AGRIMAX V- FLECTO

VF 710/75 R 42

|              |  |
|--------------|--|
| UM           | US STANDARD  |
| CONSTRUCTION |  RADIAL |
| MACHINERY    | YÜKSEK GÜÇTE TRAKTÖR / TRAKTÖR   |
| VERSION      | STANDARD   |
| TIRE TYPE    | TL   |
|              | 184 D  |



## UNDEFINED US STANDARD

|          |          |         |                  |
|----------|----------|---------|------------------|
| USA CODE | 94075447 | RC (IN) | 252.4            |
| SW (IN)  | 28.7     | RIM REC | DW 24 B          |
| OD (IN)  | 84.6     | RIM ALT | DW 23 B; DW 25 B |
| SLR (IN) | 36.9     | ECE     | E11-106R-009074  |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI                     | 9     | 12    | 15    | 17    | 20    | 23    | 29    |
|-------------------------------|-------|-------|-------|-------|-------|-------|-------|
| 45                            | 9030  | 10470 | 11920 | 13540 | 14980 | 16420 | 18050 |
| FROM 40 TO 25                 | 9920  | 11510 | 13090 | 14880 | 16470 | 18050 | 19840 |
| 20                            | 10120 | 11730 | 13350 | 15180 | 16790 | 18410 | 20240 |
| 12                            | 10320 | 11960 | 13610 | 15480 | 17120 | 18770 | 20630 |
| 5                             | 10910 | 12650 | 14400 | 16370 | 18110 | 19850 | 21820 |
| *UPTO 5 CYC WITH FRONT LOADER | 13890 | 16100 | 18330 | 20830 | 23050 | 25270 | 27780 |
| 5 HT                          | 10120 | 11730 | 13350 | 15180 | 16790 | 18410 | 20240 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.