


# MULTIMAX MP 529



<b>TIRE SIZE</b>	<b>400/70 R 20</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	ÎNCĂRCĂTOR TELESCOPIC
<b>VERSION</b>	STEEL BELTED
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	149 A8/B

## DIMENSIUNI US STANDARD

<b>USA CODE</b>	94512737	<b>RC (IN)</b>	130.5
<b>SW (IN)</b>	16.3	<b>RIM REC</b>	13
<b>OD (IN)</b>	42.9	<b>RIM ALT</b>	12 SDC;13SDC;14
<b>SLR (IN)</b>	19.7	<b>ECE</b>	E11-106R-0010769

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	23	29	35	41	46	52	58	61	64
30	3420	4020	4630	5240	5840	6500	7160	-	-
25	3420	4020	4630	5240	5840	6500	7160	-	-
20	3660	4320	4990	5670	6330	7000	7670	-	-
15	3810	4500	5190	5890	6570	7260	7960	-	-
5 CYC.	4210	5150	6080	7010	7950	8880	9820	10300	10760
STATIC	6460	7890	9330	10760	12190	13620	15060	15770	16490

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.