

AGRIMAX RT 855

TIRE SIZE	280/85 R 20
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	ОПРЫСКИВАТЕЛЬ / КОМБАЙН ДЛЯ УБОРКИ ВИНОГРАДА / ТРАКТОР-ТЯГАЧ / КОМБАЙН / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	112 A8/B



РАЗМЕРЫ US STANDARD

USA CODE	94021918	RC (IN)	116.2
SW (IN)	11.5	RIM REC	W 10
OD (IN)	38.7	RIM ALT	W 9
SLR (IN)	17.4	ECE	E4-106R-000642

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23
30	1370	1590	1810	2030	2250	2470
25	1370	1590	1810	2030	2250	2470
20	1450	1700	1940	2170	2410	2650
5 LT	1830	2130	2420	2720	3020	3320
5 HT	1450	1700	1940	2170	2410	2650

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.