

# AW 909

|                           |  |
|---------------------------|--|
| <b>TIRE SIZE</b>          | 10.0/75 - 15.3   |
| <b>UM</b>                 | US STANDARD  |
| <b>CONSTRUCTION</b>       | BIAS   |
| <b>MACHINERY</b>          | PRESĂ DE BALOTAT / MAȘINI DE IMPLEMENTARE / REMORCĂ / MAȘINĂ DE RECOLTARE / MAȘINI DE IMPLEMENTARE |
| <b>VERSION</b>            | STANDARD   |
| <b>TIRE TYPE</b>          | TL   |
| <b>LI/SS FREE ROLLING</b> | 135 A8   |



## DIMENSIUNI US STANDARD

|                 |          |                |                |
|-----------------|----------|----------------|----------------|
| <b>USA CODE</b> | 94010462 | <b>RC (IN)</b> | 87.7           |
| <b>SW (IN)</b>  | 10.8     | <b>RIM REC</b> | 9.00           |
| <b>OD (IN)</b>  | 29.9     | <b>ECE</b>     | E4-106R-001880 |
| <b>SLR (IN)</b> | 13.5     | <b>PR</b>      | 18             |

## LOAD CAPACITY (LBS/TIRE)

| <b>MPH / PSI</b> | <b>103</b> |
|------------------|------------|
| 5 FR             | 6720       |
| 15 FR            | 5720       |
| 20 FR            | 5380       |
| 25 FR            | 4810       |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.