

AGRIMAX RT 765

| | |
|---------------------|--|
| TIRE SIZE | 360/70 R 20 |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | ОПРЫСКИВАТЕЛЬ / ТРАКТОР-ТЯГАЧ / КОМБАЙН ДЛЯ УБОРКИ ВИНОГРАДА / КОМБАЙН / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 129 A8/B |



РАЗМЕРЫ US STANDARD

| | | | |
|-----------------|----------|----------------|----------------|
| USA CODE | 94021949 | RC (IN) | 122.9 |
| SW (IN) | 14.1 | RIM REC | W 11 |
| OD (IN) | 41.0 | RIM ALT | W 10; W 12 |
| SLR (IN) | 18.5 | ECE | E4-106R-000647 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 9 | 12 | 15 | 17 | 20 | 23 | 29 | 35 |
|-------------|------|------|------|------|------|------|------|------|
| 30 | 1920 | 2200 | 2540 | 2850 | 3190 | 3520 | 3800 | 4080 |
| 25 | 1920 | 2200 | 2540 | 2850 | 3190 | 3520 | 3800 | 4080 |
| 20 | 2060 | 2360 | 2710 | 3060 | 3410 | 3760 | 4070 | 4360 |
| 5 LT | 2580 | 2950 | 3390 | 3840 | 4270 | 4710 | 5090 | 5470 |
| 5 HT | 2060 | 2360 | 2710 | 3060 | 3410 | 3760 | 4070 | 4360 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.