

# FLOTATION 648

|                           |   |
|---------------------------|---|
| <b>TIRE SIZE</b>          | <b>600/55 - 26.5</b>  |
| <b>UM</b>                 | IS STANDARD   |
| <b>CONSTRUCTION</b>       | ⊠ BIAS  |
| <b>MACHINERY</b>          | ПРЕСС-ПОДБОРЩИК / КОМБАЙН<br>/ РАЗБРАСЫВАТЕЛЬ / КОМБАЙН /<br>СЕЛЬСКОХОЗЯЙСТВЕННОЕ<br>ОБОРУДОВАНИЕ |
| <b>VERSION</b>            | STANDARD  |
| <b>TIRE TYPE</b>          | TL  |
| <b>LI/SS DRIVE WHEEL</b>  | 159 A8/156 B  |
| <b>LI/SS FREE ROLLING</b> | 170 A8/167 B  |



## РАЗМЕРЫ IS STANDARD

|                 |      |                |                |
|-----------------|------|----------------|----------------|
| <b>SW (MM)</b>  | 611  | <b>RIM REC</b> | AG 20.00       |
| <b>OD (MM)</b>  | 1354 | <b>ECE</b>     | E4-106R-002276 |
| <b>SLR (MM)</b> | 581  | <b>PR</b>      | 16             |
| <b>RC (MM)</b>  | 4017 |                |                |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 2.20 | 2.40 | 2.60 |
|------------|------|------|------|
| 10 FR      | 7615 | 8015 | 8400 |
| 20 FR      | 6855 | 7215 | 7560 |
| 30 FR      | 6095 | 6410 | 6720 |
| 40 FR      | 5440 | 5725 | 6000 |
| 50 FR      | 4895 | 5155 | 5450 |
| 10 DW      | 5560 | 5845 | 6125 |
| 20 DW      | 5000 | 5260 | 5515 |
| 30 DW      | 4445 | 4675 | 4900 |
| 40 DW      | 3970 | 4175 | 4375 |
| 50 DW      | 3575 | 3760 | 4000 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.