


# AGRIMAX RT 855

<b>TIRE SIZE</b>	<b>480/80 R 50</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	FELDSPRITZE / TRAUBENERNTEMASCHINE / TRACTOR / ERNTEMASCHINE / LANDWIRTSCHAFTLICHE GERÄTE
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	159 A8/B



## ABMESSUNGEN US STANDARD

<b>USA-CODE</b>	94029914	<b>RC (IN)</b>	243.4
<b>SW (IN)</b>	19.3	<b>RIM REC</b>	DW 16 L
<b>OD (IN)</b>	80.2	<b>RIM ALT</b>	DW 15 L ; W 15 L
<b>SLR (IN)</b>	37.0	<b>ECE</b>	E4-106R-001486

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35
<b>30</b>	4540	5210	5990	6760	7530	8300	8970	9640
<b>25</b>	4540	5210	5990	6760	7530	8300	8970	9640
<b>20</b>	4860	5580	6400	7230	8060	8880	9610	10330
<b>5 LT</b>	6080	6990	8020	9060	10090	11120	12030	12930
<b>5 HT</b>	4860	5580	6400	7230	8060	8880	9610	10330

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.