

# AW 702

<b>TIRE SIZE</b>	10.0/75 - 15.3
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	▣ BIAS
<b>MACHINERY</b>	ПРЕСС-ПОДБОРЩИК / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ / ПРИЦЕП / КОМБАЙН / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ / ПРИЦЕП
<b>VERSION</b>	HD
<b>TIRE TYPE</b>	TL
<b>LI/SS FREE ROLLING</b>	135 A8



## РАЗМЕРЫ IS STANDARD

<b>SW (MM)</b>	274	<b>RIM REC</b>	9.00
<b>OD (MM)</b>	760	<b>ECE</b>	E11-106R-005317
<b>SLR (MM)</b>	351	<b>PR</b>	18
<b>RC (MM)</b>	2213		

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	7.10
10 FR	3050
25 FR	2595
30 FR	2440
40 FR	2180

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.