

# CON STAR

<b>TIRE SIZE</b>	400/70 - 20
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 BIAS
<b>MACHINERY</b>	КОМПАКТНЫЙ ПОГРУЗЧИК / ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК / КОМПАКТНЫЙ ПОГРУЗЧИК / ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК
<b>VERSION</b>	INDUSTRIAL
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	161 A8



## РАЗМЕРЫ IS STANDARD

<b>SW (MM)</b>	405	<b>RIM REC</b>	13
<b>OD (MM)</b>	1080	<b>RIM ALT</b>	12 SDC; 13 SDC; 14
<b>SLR (MM)</b>	496	<b>ECE</b>	E11-106R-0010150
<b>RC (MM)</b>	3106	<b>SRI</b>	525

## LOAD CAPACITY (KG/TIRE)

<b>KM/H / BAR</b>	<b>6.40</b>
40	4625

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.