

FLOTATION 648

TIRE SIZE	750/60 - 30.5
UM	US STANDARD
CONSTRUCTION	▣ BIAS
MACHINERY	ПРЕСС-ПОДБОРЩИК / КОМБАЙН / РАЗБРАСЫВАТЕЛЬ / КОМБАЙН / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ
VERSION	STANDARD
TIRE TYPE	TL
LI/SS DRIVE WHEEL	164 A8/160 B
LI/SS FREE ROLLING	176 A8/172 B



РАЗМЕРЫ US STANDARD

USA CODE	94006533	RC (IN)	194.3
SW (IN)	29.7	RIM REC	AG 24.00
OD (IN)	65.9	ECE	E11-106R-003410
SLR (IN)	28.0	PR	12

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	22	23	25
5 FR	20370	21150	21910
10 FR	18330	19040	19720
20 FR	16290	16930	17530
25 FR	14550	15110	15650
30 FR	13090	13600	13890
5 DW	14340	14890	15430
10 DW	12910	13400	13890
20 DW	11460	11920	12350
25 DW	10240	10640	11020
30 DW	9210	9580	9920

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.