

EARTHMAX SR 315



EARTHMAX
RADIAL OTR TIRES

EARTHMAX SR 315

SR 315 is an all steel (UMS) radial tyre specially engineered and designed for LHD. It delivers excellent performance in dig and load and carry operations in underground mines. Strong casing reinforced by multiple steel belts minimizes impact break and rock punctures. Reinforced sidewalls minimize rock cuts and damage caused by scrubbing. Specially formulated underground mine service (UMS) compound for low heat generation, reliability, protection against rock cuts and damage.



	SIZE	TT/TL	TRA CODE	STAR RATING	LI/SS	RIM		TKPH (TK/H)	OW (MM) (mm)	OD (mm)	SLR (mm)	RC (mm)	TREAD DEPTH (MM)	VERSION
						REC RIM	ALT RIM							
														
Ø25"	15.5 R 25	TL	L3S	***	182 A2	12.00/1.3	-	0	402	1265	566	3822	26	CR
Ø29"	26.5 R 29	TL	L3S	**	211 A2	22.00/3.0	-	0	725	1865	830	5635	44	CR
	26.5 R 29	TL	L3S	***	217 A2	22.00/3.0	-	0	725	1865	830	5635	44	CR

CR: CUT RESISTANT COMPOUND

TECHNOLOGIES					PERFORMANCES			
								

Permissible tolerances: O.O. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tyre width O.O. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balakrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

GB – 23/09/2026



TECHNOLOGIES		PERFORMANCES	
	 L3S		
	 217 kg		

Permissible tolerances: O.O. 2%-S.W. 2%-RC 2.5%-LI/SS load/speed index, S.W. tyre width O.O. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. BKRishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.