


# AGRIMAX V-FLECTO

<b>TYRE SIZE</b>	<b>VF 710/70 R 42</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	HIGH-POWER TRACTOR / TRACTOR
<b>VERSION</b>	STEEL BELTED SPL
<b>TYRE TYPE</b>	TL



## DIMENSIONS IS STANDARD

<b>SW (MM)</b>	720	<b>RIM REC</b>	DW 25 B
<b>OD (MM)</b>	2058	<b>RIM ALT</b>	DW 23 B; DW 24 B
<b>SLR (MM)</b>	928	<b>ECE</b>	E11-106R-009053
<b>RC (MM)</b>	6233	<b>SRI</b>	975

## LOAD CAPACITY (KG/TYRE)

KM/H / BAR	0.6	0.8	1	1.2	1.4	1.6	2	2.4	2.8	3.2	3.6
70	3875	4500	5130	5865	6490	7120	7850	8270	9105	9840	10465
FROM 65 TO 40	4255	4945	5635	6440	7130	7820	8625	9085	10005	10810	11500
30	4345	5045	5750	6570	7275	7980	8800	9270	10210	11030	11730
20	4430	5145	5865	6700	7420	8135	8970	9450	10410	11245	11960
10	4685	5440	6200	7085	7845	8605	9490	9995	11010	11895	12650
UPTO 30 CYC	4830	5615	6395	7310	8095	8875	9790	10310	11355	12270	13050
UPTO 15 CYC	5765	6700	7635	8725	9660	10595	11685	12310	13555	14650	15580
UPTO 10 CYC	6320	7345	8370	9565	10590	11615	12810	13490	14860	16055	17075
10HT	4345	5045	5750	6570	7275	7980	8800	9270	10210	11030	11730

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.