

# LG 306

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | <b>31X15.5 - 15</b>                    |
| <b>UM</b>           | IS STANDARD                            |
| <b>CONSTRUCTION</b> | ⊠ BIAS                                 |
| <b>MACHINERY</b>    | RASENMÄHER / KLEINTRAKTOR /<br>TRACTOR |
| <b>VERSION</b>      | STANDARD                               |
| <b>TIRE TYPE</b>    | TL                                     |



## ABMESSUNGEN IS STANDARD

|                 |      |                |                 |
|-----------------|------|----------------|-----------------|
| <b>SW (MM)</b>  | 391  | <b>RIM REC</b> | 13 LB           |
| <b>OD (MM)</b>  | 792  | <b>ECE</b>     | E11-106R-004083 |
| <b>SLR (MM)</b> | 372  | <b>PR</b>      | 4               |
| <b>RC (MM)</b>  | 2305 |                |                 |

## LOAD CAPACITY (KG/TIRE)

|                   |             |
|-------------------|-------------|
| <b>KM/H / BAR</b> | <b>1.40</b> |
| 50                | 775         |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.