

# BK 826

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | <b>9.00 - 16</b>   |
| <b>UM</b>           | US STANDARD  |
| <b>CONSTRUCTION</b> | ⊠ BIAS   |
| <b>MACHINERY</b>    | ANHÄNGER / LANDWIRTSCHAFTLICHE<br>GERÄTE / ERNTEMASCHINE /<br>ANHÄNGER / BAGGERLADER |
| <b>VERSION</b>      | TRACTOR TRAILER  |
| <b>TIRE TYPE</b>    | TT   |
| <b>LI/SS</b>        | 138 A6   |



## ABMESSUNGEN US STANDARD

|                 |          |                |                 |
|-----------------|----------|----------------|-----------------|
| <b>USA-CODE</b> | 94047017 | <b>RIM ALT</b> | 6.00 G          |
| <b>SW (IN)</b>  | 10.4     | <b>ECE</b>     | E11-106R-005356 |
| <b>OD (IN)</b>  | 36.4     | <b>PR</b>      | 18              |
| <b>RIM REC</b>  | 6.50 H   |                |                 |

## LOAD CAPACITY (LBS/TIRE)

|                  |            |
|------------------|------------|
| <b>MPH / PSI</b> | <b>110</b> |
| 20               | 5200       |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.