


# AGRIMAXFACTOR



	<b>600/70 R 28</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	TRAKTÖR
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
	157 D ; 160 A8

## UNDEFINED IS STANDARD

<b>SW (MM)</b>	611	<b>RIM REC</b>	DW 20 B
<b>OD (MM)</b>	1551	<b>RIM ALT</b>	DW 18 L; W 18 L
<b>SLR (MM)</b>	714	<b>ECE</b>	E11-106R-007655
<b>RC (MM)</b>	4667	<b>SRI</b>	725

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
65	1940	2230	2560	2890	3220	3550	3880	4125
50	2040	2345	2690	3035	3385	3730	4075	4335
40	2125	2445	2805	3165	3530	3890	4250	4520
30	2235	2565	2945	3325	3705	4085	4465	4745
10 LT	2600	2990	3430	3875	4315	4760	5200	5530
10HT	2235	2565	2945	3325	3705	4085	4465	4745

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.