

AGRIMAX RT 855

TIRE SIZE	480/80 R 50
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	ОПРЫСКИВАТЕЛЬ / КОМБАЙН ДЛЯ УБОРКИ ВИНОГРАДА / ТРАКТОР-ТЯГАЧ / КОМБАЙН / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ
VERSION	STEEL BELTED
TIRE TYPE	TL
LI/SS	176 A8



РАЗМЕРЫ US STANDARD

USA CODE	94045358	RC (IN)	243.4
SW (IN)	19.3	RIM REC	DW 16 L
OD (IN)	80.2	RIM ALT	DW 15 L; W 15 L
SLR (IN)	37.2	ECE	E4-106R-001495

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35	41	46	52	58	64	73
30	4540	5210	5990	6760	7530	8300	8970	9640	10490	11430	12060	12840	13930	15650
25	4540	5210	5990	6760	7530	8300	8970	9640	10490	11430	12060	12840	13930	15650
20	4860	5580	6400	7230	8060	8880	9610	10330	11230	12230	12910	13750	14910	16750
5 LT	6080	6990	8020	9060	10090	11120	12030	12930	14060	15320	16160	17210	18670	20980
5 HT	4860	5580	6400	7230	8060	8880	9610	10330	11230	12230	12910	13750	14910	16750

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.