DATA SHEET

PRINTED ON
23-04-2026

EARTHMAX SR 22

TIRE SIZE	**20.5 R 25**
UM	US STANDARD
CONSTRUCTION	
MACHINERY	GRADER / LOADER / DOZER / LOADER / DOZER / GRADER
VERSION	CUT RESISTANT COMPOUND
TIRE TYPE	TL
LI/SS	161 A8 ; 186 A2

DIMENSIONS US STANDARD

USA CODE	94040803	**RIM REC**	17.00/2.0
OD (IN)	58.7	**RIM ALT**	17.00/1.7
SLR (IN)	25.2	**TRA CODE**	G2/L2
RC (IN)	169.9	**STAR RATING**	★

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	18	22	25	29	33	36	40	44	58	62	65	69	73
25	5360	6150	6950	7600	8550	9100	9650	10200	-	-	-	-	-
5	-	-	-	-	-	-	-	-	17600	18200	19300	19800	20900

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..