


RIDEMAX FL 693 M



| | |
|---------------------|--|
| TIRE SIZE | 650/55 R 26.5 |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | TANKBIL / SLÄPVAGN / ARBETSFORDON |
| VERSION | HD |
| TIRE TYPE | TL |
| LI/SS | 178 D |

DIMENSIONER IS STANDARD

| | | | |
|-----------------|------|----------------|-----------------|
| SW (MM) | 645 | RIM REC | AG 20.00 |
| OD (MM) | 1389 | ECE | E11-106R-003008 |
| SLR (MM) | 615 | SRI | 650 |
| RC (MM) | 4250 | | |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 1.0 | 1.2 | 1.6 | 2.0 | 2.4 | 2.8 | 3.2 | 3.6 | 4.0 | 5.0 | 6.0 |
|------------|------|------|------|------|------|------|------|-------|-------|-------|-------|
| 65 | 2325 | 2775 | 3375 | 3900 | 4500 | 5100 | 5475 | 6075 | 6675 | 7050 | 7500 |
| 50 | 2815 | 3360 | 4085 | 4720 | 5445 | 6175 | 6625 | 7355 | 8080 | 8535 | 9075 |
| 40 | 3165 | 3775 | 4590 | 5305 | 6120 | 6940 | 7450 | 8265 | 9080 | 9590 | 10200 |
| 30 | 3515 | 4195 | 5100 | 5890 | 6795 | 7705 | 8270 | 9175 | 10080 | 10650 | 11325 |
| 25 | 3675 | 4385 | 5335 | 6165 | 7110 | 8060 | 8655 | 9600 | 10550 | 11140 | 11850 |
| 10 | 4185 | 4995 | 6075 | 7020 | 8100 | 9180 | 9855 | 10935 | 12015 | 12690 | 13500 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.