


# RIDEMAX FL 693 M



<b>TIRE SIZE</b>	<b>600/55 R 26.5</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	CAMIÓN CISTERNA / REMOLQUE / MAQUINARIA AGRÍCOLA
<b>VERSIÓN</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	165 D

## DIMENSIONES US STANDARD

<b>CÓDIGO USA</b>	94047277	<b>RC (IN)</b>	159.5
<b>SW (IN)</b>	24.1	<b>RIM REC</b>	AG 20.00
<b>OD (IN)</b>	52.5	<b>ECE</b>	E4-106R-002398
<b>SLR (IN)</b>	23.1		

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	15	17	23	29	35	41	46	52	58
45	3840	4340	5280	6110	7030	7970	8590	9510	10340
40	4210	4770	5800	6700	7730	8750	9420	10450	11350
30	5090	5780	7010	8110	9350	10590	11420	12650	13750
25	5720	6490	7880	9120	10500	11890	12820	14210	15440
15	6650	7540	9160	10590	12210	13820	14900	16510	17940
5	7570	8590	10430	12060	13900	15740	16960	18800	20440

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.