


AGRIMAXFACTOR

| | |
|---------------------|--|
| TIRE SIZE | 580/70 R 42 |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | TRACTOR |
| VERSION | STANDARD |
| TL/TT | TL |
| LI/SS | 158 D ; 161 A8 |



DIMENSIONS IS STANDARD

| | | | |
|-----------------|------|----------------|------------------|
| SW (MM) | 577 | RIM REC | W 18 L |
| OD (MM) | 1879 | RIM ALT | DW18L;DD18L |
| SLR (MM) | 856 | ECE | E11-106R-0010076 |
| RC (MM) | 5693 | SRI | 900 |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.6 | 0.8 | 1 | 1.2 | 1.4 | 1.6 |
|------------|------|------|------|------|------|------|
| 65 | 2340 | 2720 | 3105 | 3485 | 3870 | 4250 |
| 50 | 2460 | 2860 | 3260 | 3665 | 4065 | 4465 |
| 40 | 2545 | 2960 | 3380 | 3795 | 4210 | 4625 |
| 30 | 2690 | 3130 | 3570 | 4010 | 4450 | 4890 |
| 10 LT | 3135 | 3645 | 4160 | 4670 | 5185 | 5695 |
| 10HT | 2690 | 3130 | 3570 | 4010 | 4450 | 4890 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.