

FLOTATION 558

TIRE SIZE	500/45 - 22.5
UM	IS STANDARD
CONSTRUCTION	⊠ BIAS
MACHINERY	PRESĂ DE BALOTAT / MAȘINĂ DE RECOLTARE / CISTERNĂ / REMORCĂ / MAȘINĂ DE RECOLTARE / MAȘINI DE IMPLEMENTARE
VERSION	STANDARD
TIRE TYPE	TL
LI/SS DRIVE WHEEL	146 A8/142 B
LI/SS FREE ROLLING	158 A8/154 B



DIMENSIUNI IS STANDARD

SW (MM)	500	RIM REC	AG 16.00
OD (MM)	1045	ECE	E11-106R-005353
SLR (MM)	471	PR	20
RC (MM)	3167		

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	4.30	4.40	4.50
10 FR	5795	5875	5950
20 FR	5215	5285	5355
30 FR	4635	4700	4760
40 FR	4140	4195	4250
50 FR	3725	3775	3750
10 DW	4090	4145	4200
20 DW	3680	3730	3780
30 DW	3270	3315	3360
40 DW	2920	2960	3000
50 DW	2630	2665	2650

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.