


AGRIMAX V-FLECTO

TIRE SIZE	VF 600/60 R 38
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	ТРАКТОР ВЫСОКОЙ МОЩНОСТИ / ТРАКТОР-ТЯГАЧ
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	166 D



РАЗМЕРЫ IS STANDARD

SW (MM)	587	RIM REC	DW 20 B
OD (MM)	1685	RIM ALT	DW 18 L
SLR (MM)	757	ECE	E11-106R-005021
RC (MM)	5081	SRI	800

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0
70	2360	2745	3180	3565	3950	4340	4820
FROM 65 TO 40	2595	3020	3495	3920	4345	4770	5300
30	2645	3080	3560	3995	4430	4865	5405
20	2695	3140	3630	4075	4515	4960	5510
10	2850	3320	3840	4310	4775	5245	5830
*UPTO 10 CYC WITH FRONT LOADER	3630	4225	4890	5485	6080	6675	7420
10HT	2645	3080	3560	3995	4430	4865	5405

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.