

# AW 702

|                           |  |
|---------------------------|--|
| <b>TIRE SIZE</b>          | <b>13.0/65 - 18</b>  |
| <b>UM</b>                 | US STANDARD  |
| <b>CONSTRUCTION</b>       |  BIAS |
| <b>MACHINERY</b>          | BALPRESS / ARBETSFORDON /<br>SLÄPVAGN / SKÖRDEMASKIN /<br>ARBETSFORDON / SLÄPVAGN      |
| <b>VERSION</b>            | STANDARD   |
| <b>TIRE TYPE</b>          | TT   |
| <b>LI/SS FREE ROLLING</b> | 141 A8   |



## DIMENSIONER US STANDARD

|                 |          |                |                 |
|-----------------|----------|----------------|-----------------|
| <b>USA CODE</b> | 94009749 | <b>RC (IN)</b> | 102.7           |
| <b>SW (IN)</b>  | 13.2     | <b>RIM REC</b> | 11.0            |
| <b>OD (IN)</b>  | 35.0     | <b>ECE</b>     | E11-106R-004248 |
| <b>SLR (IN)</b> | 15.7     | <b>PR</b>      | 14              |

## LOAD CAPACITY (LBS/TIRE)

| <b>MPH / PSI</b> | <b>62</b> |
|------------------|-----------|
| <b>5 FR</b>      | 7950      |
| <b>15 FR</b>     | 6760      |
| <b>20 FR</b>     | 6360      |
| <b>25 FR</b>     | 5680      |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.