

FLOTATION 648

TIRE SIZE	500/60 - 22.5
UM	US STANDARD
CONSTRUCTION	⊠ BIAS
MACHINERY	BALER / HAY HARVESTER / SPREADER / HARVESTER / IMPLEMENTS
VERSION	STANDARD
TIRE TYPE	TL
LI/SS DRIVE WHEEL	151 A8/148 B
LI/SS FREE ROLLING	163 A8/159 B



DIMENSIONS US STANDARD

USA CODE	94006359	RC (IN)	137.4
SW (IN)	19.7	RIM REC	AG 16.00
OD (IN)	46.1	RIM ALT	15.00; 17.00
SLR (IN)	20.1	ECE	E4-106R-002308

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	41	44	46
5 FR	13920	14490	15050
10 FR	12530	13040	13550
20 FR	11130	11600	12040
25 FR	9940	10350	10750
30 FR	8950	9310	9640
5 DW	9840	10250	10650
10 DW	8860	9230	9580
20 DW	7880	8200	8520
25 DW	7030	7320	7610
30 DW	6330	6590	6940

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.