


# AGRIMAX V- FLECTO

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | <b>VF 520/85 R 50 CFO</b>  |
| <b>UM</b>           | IS STANDARD  |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | ТРАКТОР-ТЯГАЧ / ТРАКТОР<br>ВЫСОКОЙ МОЩНОСТИ  |
| <b>VERSION</b>      | STEEL BELTED SPL   |
| <b>TIRE TYPE</b>    | TL   |
| <b>LI/SS</b>        | 177 D  |



## РАЗМЕРЫ IS STANDARD

|                 |      |                |                  |
|-----------------|------|----------------|------------------|
| <b>SW (MM)</b>  | 535  | <b>RIM REC</b> | DW 18 L          |
| <b>OD (MM)</b>  | 2160 | <b>RIM ALT</b> | DW 16 L          |
| <b>SLR (MM)</b> | 972  | <b>ECE</b>     | E11-106R-0011305 |
| <b>RC (MM)</b>  | 6493 | <b>SRI</b>     | 1025             |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR    | 0.6  | 0.8  | 1.0  | 1.2  | 1.4  | 1.6  | 2.0   | 2.4   |
|---------------|------|------|------|------|------|------|-------|-------|
| 70            | 3120 | 3585 | 4115 | 4645 | 5175 | 5710 | 6240  | 6640  |
| FROM 65 TO 40 | 3430 | 3940 | 4525 | 5110 | 5690 | 6275 | 6860  | 7300  |
| 30            | 3495 | 4020 | 4615 | 5210 | 5805 | 6400 | 6995  | 7445  |
| 20            | 3565 | 4095 | 4705 | 5310 | 5920 | 6525 | 7130  | 7590  |
| 10            | 3770 | 4335 | 4975 | 5620 | 6260 | 6905 | 7545  | 8030  |
| UPTO 30 CYC   | 3890 | 4470 | 5135 | 5795 | 6460 | 7125 | 7785  | 8285  |
| UPTO 15 CYC   | 4645 | 5340 | 6130 | 6920 | 7710 | 8505 | 9295  | 9890  |
| UPTO 10 CYC   | 5090 | 5850 | 6720 | 7585 | 8455 | 9320 | 10185 | 10840 |
| 10 HT         | 3495 | 4020 | 4615 | 5210 | 5805 | 6400 | 6995  | 7445  |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.