

## MP 600

|                          |                                                                                        |
|--------------------------|----------------------------------------------------------------------------------------|
| <b>TIRE SIZE</b>         | <b>400/70 - 24</b>                                                                     |
| <b>UM</b>                | IS STANDARD                                                                            |
| <b>CONSTRUCTION</b>      |  BIAS |
| <b>MACHINERY</b>         | IMPLEMENT MACHINERY /<br>TELEHANDLER / IMPLEMENTS /<br>TELEHANDLER / UNIVERSAL VEHICLE |
| <b>VERSION</b>           | STANDARD                                                                               |
| <b>TIRE TYPE</b>         | TL                                                                                     |
| <b>LI/SS DRIVE WHEEL</b> | 158 A8                                                                                 |



### DIMENSIONS IS STANDARD

|                 |      |                |                 |
|-----------------|------|----------------|-----------------|
| <b>SW (MM)</b>  | 405  | <b>RIM REC</b> | 13 SDC          |
| <b>OD (MM)</b>  | 1185 | <b>RIM ALT</b> | 12              |
| <b>SLR (MM)</b> | 545  | <b>ECE</b>     | E11-106R-003641 |
| <b>RC (MM)</b>  | 3530 | <b>PR</b>      | 18              |

### LOAD CAPACITY (KG/TIRE)

|                   |             |
|-------------------|-------------|
| <b>KM/H / BAR</b> | <b>4.50</b> |
| <b>40 DW</b>      | 4250        |
| <b>50 DW</b>      | 4125        |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.