

EARTHMAX SR 41



EARTHMAX
RADIAL OTR TIRES

EARTHMAX SR 41

EARTHMAX SR 41 is an All Steel radial tyre perfect for Articulated Dump Trucks, Loaders and Dozers. Thanks to its all steel structure and special block pattern, EARTHMAX SR 41 provides excellent resistance against punctures and an extended service life. In addition to long working hours without downtime, the tyre ensures extraordinary comfort. EARTHMAX SR 41 is also available in E4*** for Low Profile Dump Trucks (LPDT) used in underground haulage operations.



	SIZE	TT/TL	TRA CODE	STAR RATING	LI/SS	RIM		TKPH (TK/H)	OW (MM) (mm)	OD (mm)	SLR (mm)	RC (mm)	TREAD DEPTH (MM)	VERSION
						REC RIM	ALT RIM							
														
Ø25"	29.5 R 25	TL	SH4	****	-	25.00/3.5	-	0	761	1861	830	5510	66	CR
	29.5 R 25	TL	E4	**	200 B	25.00/3.5	-	285	761	1861	830	5510	66	STD
	29.5 R 25 (SW - 772 , OD- 1862)	TL	E4/L4	**/*	200 B 208 A2	25.00/3.5	-	225	772	1862	830	5510	66	CR
	23.5 R 25	TL	E4/L4	**/*	185 B 195 A2	19.50/2.5	-	161	615	1611	725	4790	53	CR

CR: CUT RESISTANT COMPOUND, STD: STANDARD

TECHNOLOGIES					PERFORMANCES			
								
	E4/L4/SH4							
								
B	221 kg							

Permissible tolerances: O.D. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tyre width O.O. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balkrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

GB – 23/09/2026

	SIZE	TT/TL	TRA CODE	STAR RATING	LI/SS	RIM		TKPH (TK/H)	OW (MM) (mm)	OD (mm)	SLR (mm)	RC (mm)	TREAD DEPTH (MM)	VERSION
						REC RIM	ALT RIM							
														
	26.5 R 25	TL	E4/L4	**/*	193 B 202 A2	22.00/3.0	-	185	678	1742	775	5150	59	CR
	26.5 R 25	TL	E4	**	193 B	22.00/3.0	-	235	678	1742	775	5150	59	STD
	29.5 R 25	TL	E4/L4	**/*	200 B 208 A2	25.00/3.5	-	225	761	1861	830	5510	66	CR
	29.5 R 25	TL	E4	**	200 B	25.00/3.5	-	225	761	1861	830	5510	66	CR
	26.5 R 25	TL	SH4	****	-	22.00/3.0	-	0	678	1742	775	5150	59	CR
	29.5 R 25	TL	L4	***	221 A2	25.00/3.5	-	0	761	1861	830	5510	66	CR
Ø29"	875/65 R 29 (35/65 R 29)	TL	L4	**	221 A2	27.00/3.5	27.00/3.0 28.00/3.5	0	880	1865	837	5680	60	CR
	875/65 R 29 (35/65 R 29)	TL	E4/L4	**/*	203 B 214 A2	27.00/3.50	27.00/3.0 28.00/3.5	240	880	1865	837	5680	60	CR
	875/65 R 29 (35/65 R 29)	TL	E4	**	203 B	27.00/3.50	27.00/3.0 28.00/3.5	240	880	1865	837	5680	60	CR

CR: CUT RESISTANT COMPOUND, STD: STANDARD

TECHNOLOGIES					PERFORMANCES			
								

Permissible tolerances: O.D. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tyre width O.O. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balakrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

GB – 23/09/2026

	SIZE	TT/TL	TRA CODE	STAR RATING	LI/SS	RIM		TKPH (TK/H)	OW (MM) (mm)	OD (mm)	SLR (mm)	RC (mm)	TREAD DEPTH (MM)	VERSION
						REC RIM	ALT RIM							
														
	875/65 R 29 (35/65 R 29)	TL	L4	*	214 A2	27.00/3.50	27.00/3.0 28.00/3.5	0	880	1865	837	5680	60	CR
Ø33"	35/65 R33	TL	SH4	****	-	28.00/3.5	--	0	896	2063	926	6283	62	CR

CR: CUT RESISTANT COMPOUND, STD: STANDARD



TECHNOLOGIES				PERFORMANCES			
							
	E4/L4/SH4						
							
B	221 kg						

Permissible tolerances: O.D. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tyre width O.O. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balakrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

GB – 23/09/2026