


# AGRIMAX RT 955

<b>TIRE SIZE</b>	230/95 R 42
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	FELDSPRITZE / TRAUBENERNTEMASCHINE / ERNTEMASCHINE / LANDWIRTSCHAFTLICHE GERÄTE
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	133 A8/B



## ABMESSUNGEN US STANDARD

<b>USA-CODE</b>	94028610	<b>RC (IN)</b>	180.9
<b>SW (IN)</b>	9.0	<b>RIM REC</b>	W 7
<b>OD (IN)</b>	59.3	<b>RIM ALT</b>	W 8
<b>SLR (IN)</b>	28.1	<b>ECE</b>	E4-106R-000772

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	12	17	23	29	35	41	46	52	58	64
30	1770	2330	2820	3100	3270	3590	3910	4230	4530	-
25	1770	2330	2820	3100	3270	3590	3910	4230	4530	-
20	1900	2480	3020	3310	3510	3850	4190	4530	4860	-
5	2120	2670	3270	3890	4500	4640	5180	5730	6270	6810

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.