

EARTHMAX SR 431



EARTHMAX
RADIAL OTR TIRES

EARTHMAX SR 431



EARTHMAX SR 431 (E-4) is an All Steel tire specially designed for rigid haul trucks operating in severe mining conditions (surface and underground mines). The non-directional tread pattern ensures excellent traction and stability. The tire features a strong All Steel casing and a special tread compound providing extraordinary cut and chip resistance as well as a long service life even in rocky, abrasive and harsh environments.



SIZE	TT/TL	TRA CODE	STAR RATING	LI/SS	RIM		TMPH	O.W. (in)	OD (in)	SLR (in)	RC (in)	THREAD DEPTH	VERSION
					REC RIM	ALT RIM							
													
Ø25"	16.00 R 25	TL	E4	**	-	11.25/2.0	-	0	17.8	60.3	28.1	183.0	CRC UMS
	18.00 R 25	TL	SH4	****	-	13.00/2.5	-	0	20.5	65.4	29.9	198.4	CR
	18.00 R 25	TL	E4	**	185 B	13.00/2.5	-	96	20.5	65.4	29.9	198.4	CR
	16.00 R 25	TL	E4	**	177 B	11.25/2.0	-	114	17.8	60.3	28.1	183.0	CR
	16.00 R 25	TL	E4	***	183 B	11.25/2.0	-	114	17.8	60.3	28.1	183.0	CR

CRC UMS: CUT RESISTANT COMPOUND (UMS), CR: CUT RESISTANT COMPOUND

TECHNOLOGIES		PERFORMANCES	
 E4/SH4	 B	 185 lbs	

Permissible tolerances: 0.0. 2%-S.W. 2%-RC 2.5%-LI/SS load/speed index, S.W. tire width 0.0, outer diameter of the tire: SLR static radius, RC rolling circumference ; SRI index