


# AGRIMAX FORTIS



|                     |  |
|---------------------|--|
| <b>TYRE SIZE</b>    | <b>600/70 R 34</b>   |
| <b>UM</b>           | US STANDARD  |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | TRACTOR  |
| <b>VERSION</b>      | STANDARD   |
| <b>TL/TT</b>        | TL   |
| <b>LI/SS</b>        | 160 D ; 163 A8   |

## DIMENSIONS US STANDARD

|                 |          |                |                  |
|-----------------|----------|----------------|------------------|
| <b>USA CODE</b> | 94035649 | <b>RC (IN)</b> | 201.1            |
| <b>SW (IN)</b>  | 23.3     | <b>RIM REC</b> | DW 18 L          |
| <b>OD (IN)</b>  | 67.1     | <b>RIM ALT</b> | DW 20 B ; W 18 L |
| <b>SLR (IN)</b> | 30.0     | <b>ECE</b>     | E4-106R-001401   |

## LOAD CAPACITY (LBS/TYRE)

| MPH / PSI | 9    | 12   | 15   | 17   | 20    | 23    | 29    | 35    |
|-----------|------|------|------|------|-------|-------|-------|-------|
| 40        | 4760 | 5560 | 6250 | 6940 | 7640  | 8230  | 9130  | 9920  |
| 30        | 5000 | 5840 | 6570 | 7300 | 8020  | 8650  | 9590  | 10420 |
| 25        | 5160 | 6020 | 6780 | 7530 | 8280  | 8930  | 9890  | 10750 |
| 20        | 5480 | 6390 | 7200 | 7990 | 8780  | 9480  | 10500 | 11410 |
| 5 LT      | 6380 | 7450 | 8380 | 9310 | 10240 | 11030 | 12230 | 13290 |
| 5 HT      | 5480 | 6390 | 7200 | 7990 | 8780  | 9480  | 10500 | 11410 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.