

AGRIMAX RT 657

TIRE SIZE	900/55 R 38
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	КОМБАЙН ДЛЯ УБОРКИ ВИНОГРАДА / ТРАКТОР-ТЯГАЧ / КОМБАЙН
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	179 D ; 181 A8



РАЗМЕРЫ US STANDARD

USA CODE	94067534	RC (IN)	230.0
SW (IN)	34.6	RIM REC	DW 27 B
OD (IN)	76.8	RIM ALT	DW 30 B
SLR (IN)	34.6	ECE	E11-106R-006946

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35	41
40	7180	8380	9400	10590	11790	12980	14530	15550	17100
30	7540	8800	9880	11130	12390	13650	15260	16340	17940
25	7640	8920	10010	11280	12550	13820	15460	16560	18200
20	8260	9630	10810	12190	13570	14950	16710	17890	19650
5 LT	9620	11220	12600	14200	15810	17400	19470	20840	22890
5 HT	8260	9630	10810	12190	13570	14950	16710	17890	19650

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.