

EARTHMAX SR 45



EARTHMAX
RADIAL OTR TIRES

EARTHMAX SR 45

EARTHMAX SR 45 is an All Steel radial tyre specially designed for rigid haul trucks. EARTHMAX SR 45 is the ideal tyre for all operations requiring high traction.



SIZE	TT/TL	TRA CODE	STAR RATING	LI/SS	RIM		TKPH (TK/H)	OW (MM) (mm)	OD (mm)	SLR (mm)	RC (mm)	TREAD DEPTH (MM)	VERSION	
					REC RIM	ALT RIM								
														
Ø33"	18.00 R 33	TL	E4	**	191 B	13.00/2.5	--	185	505	1870	856	5608	55	CR

CR: CUT RESISTANT COMPOUND



TECHNOLOGIES					PERFORMANCES			
								
E4								
B								
191 kg								

Permissible tolerances: O.D. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tyre width O.O. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balakrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

GB – 23/09/2026